



## Condé® Pumps Specifics

Specifications	Model 3	Model 6	Super 6	SDS 6	SDS12
Free Air capacity	20 CFM	40 CFM	70 CFM	115 CFM	180 CFM
Maximum Vacuum	27" HG	27" HG	27" HG	27" HG	27" HG
Maximum Pressure	20 psi	20 psi	20 psi	20 psi	20 psi
Normal Operating Pressure	5-10 psi	5-10 psi	5-10 psi	5-10 psi	5-10 psi
BHP at Full vacuum	2 HP	5 HP	5 HP	7.5 HP	11.5 HP
Lubrication	Automatic	Automatic	Automatic	Automatic	Automatic
Operating Speed	1100-1750	1100-1750	1200-1750	1100-1750	1100-1750
Shaft Diameter	1"	1"	1"	1"	1 1/8"
Weight	18 kg	29 kg	32 kg	47 kg	68 kg
Ideal Tank Size (Litres)	75-760	760-1520	1100-3000	1500-3800	1900-7600
Available in pressure models	No	No	Yes	Yes	Yes

1800 766 933 – [www.portabletoilets.net.au](http://www.portabletoilets.net.au) – [sales@portabletoilets.net.au](mailto:sales@portabletoilets.net.au)